

Package: ShinyWizard (via r-universe)

October 29, 2024

Title An Interactive Wizard to Design, Build, and Deploy R Packages
Demo Presentation

Version 1.1.3.11

Description Design, build, and deploy R packages demo presentations by an interactive wizard. Set up unique title, logo and themes. Add personalized tabs exposing applicability. And deploy as a part of a package or an independent app.

License GPL (>= 3)

Encoding UTF-8

Imports base, rstudioapi

RoxygenNote 7.3.2

Suggests testthat (>= 3.0.0), devtools, shinythemes, shinydashboard, shinyWidgets, shinyjs, yaml, readr, stringr, bslib, reshape2, shinytest2

Config/testthat/edition 3

NeedsCompilation no

Author Rafal Urniaz [aut, cre]
(<<https://orcid.org/0000-0003-0192-2165>>)

Maintainer Rafal Urniaz <rafal.urniaz@cantab.net>

Date/Publication 2024-10-28 13:00:02 UTC

Repository <https://r3pos.r-universe.dev>

RemoteUrl <https://github.com/cran/ShinyWizard>

RemoteRef HEAD

RemoteSha a851990d03b3d840b530ea0981a4a6b86cd2e879

Contents

RunShinyWizard	2
Index	3

RunShinyWizard	<i>Run ShinyWizard builder / project app</i>
----------------	--

Description

Function executes ShinyWizard builder when file location is not provided or project app when project zip file location is provided.

Usage

```
RunShinyWizard(loc = NULL, devMode = FALSE)
```

Arguments

loc	file path to app file (*.zip), when NULL runs builder
devMode	when TRUE the developer mode is used. It means all tasks run by separate background jobs and the console is not blocked. It works by R Studio API so works only with R studio. It is mode only for development facilitate. Should not be used for production when compatibility with pure R is required.

Value

No return value, executes R shiny app

Examples

```
# Run to execute ShinyWizard builder
RunShinyWizard()

# Run to execute saved project as zip file
RunShinyWizard("Path-to-project-file")
```

Index

RunShinyWizard, [2](#)